

## Specifications

	G3-32X
1 Km Error	$\leq 1.5\text{mm}$
Magnification	32x
Objective Aperture	42mm
Resolving Power	$\leq 3.5''$
Angle of View	1" 20'
Image	Erect
Reticle	Cross Reticle (Wedge Option)
<b>Min view Distance</b>	$\leq 0.3\text{m}$
View Distance Error	$\leq \pm 0.4\%$
Focusing Error	$\leq 0.5\text{m}$
<b>Automatic Compensator</b>	<b>Magneticdamper</b>
Working Range	$\leq \pm 15'$
<b>Compensating Error</b>	$\leq 0.3''$
Setting Accuracy	$\leq 0.5''$
Setting Time	$\leq 2\text{s}$
Bubble	10' / 2mm
Scale	1° or 1 log
Water Resistance	JIS C 0920 ip x6
Weight	Level N.W.: 1.8 Kgs Level G.W.: 3 Kgs
Package	Plastic case small carton, four small cartons packed in a big carton. Big carton size: 41.5 cm * 31.5 cm * 41 cm
Size Width	130 mm (5.12 IN.)
Size Length	215 mm (8.46 in.)
Size Height	140 mm (5.51 in.)
Weight	1.85 Kg (4.1 lbs)